Technical Data

634

Electronic Hour Meter, DC Hour Meter

T40 Series





T40A45, T40B45

<u>Features</u>

- Low Power Consumption
- Solid State Electronic Drive Circuit
- Quartz-Crystal for Accurate Timing
- Non-reset
- UL/cUL Recognized, CE & RoHS Compliant
- High Impact, Tamperproof Plastic Case
- IP67
- Indicates Operating Time in Hours and Tenths
- No Battery Back-Up Required
- Quiet operation
- MADE IN THE U.S.A.

ENM's T40 Series: Low Power DC Hour Meter is the answer to applications requiring a low power, low cost reliable hour meter. This compact tamperproof meter is sealed against the environment to provide years of service.

Accumulated hours are stored in the mechanical indicating counter; therefore, no battery is required to maintain elapsed time.

The T40 contains an input diode for polarity protection.

A quartz-crystal time base insures accurate long term timekeeping.

Specifications	
Time Scale:	6-digits 99,999.9 Hours Automatic recycle to zero
Figures:	Hours - White on black Tenths - Black on white Height - 0.140"
Operation Voltage:	Extended range 4-40 VDC, polarity protected and 10-80 vdc, polarity insensitive
Power Consumption:	Less than .03 Watts at 12V DC .7 Watts at 48V DC
Accuracy:	Better than ±0.02% over entire range
Temperature:	-40°F to +185°F (-40°C to +85°C)
Vibration Resistance:	Withstands 10-80 Hz at 20g's max. (SAE J1378)
Shock:	55g at 9-13 ms (SAE J1378)
Humidity:	95% (SAE J1378)
Terminations:	1/4" male blade terminals
Protected from:	Alternator load dump inductive switching
Configuration:	Round SAE Bezel with new push-on retaining ring Round 3-Hole Bezel

2013 ENM Co.®



ENM Company

5617 Northwest Highway, Chicago, IL 60646-6135

(773) 775-8400 • Fax: (773) 775-5968

Toll Free (888) 372-0465 • e-mail: customerservice@enmco.com

web site: www.enmco.com



T40 Series


Dimensional Data

634


T40 Series


Available to facilitate installation are: Two 12" long wires with insulated quick disconnects and quick disconnect screw terminals.





(T40 B)











PANEL GASKET; UL/NEMA 4X12 WITH MTG


HARDWARE; P/N B20017














2013 ENM Co.®

LIMITED WARRANTY

ENM Company resettable electromechanical counters are warranted to the consumer to be free from defects in material and workmanship for a period of 3 years. All ENM products which fall within the warranty period due to defects in material or workmanship will be repaired or replaced, at ENM's option, without charge to the consumer when returned with proof of purchase to any authorized ENM dealer in the United States, transportation charges prepaid, provided there is no evidence of improper installation, tampering, or other abuse. All implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, shall be limited in duration to the express warranty period specified above. ENM disclaims any liability for consequential damages due to breach of any written or implied warranty on its products. Datasheet information subject to change.



ENM Company

5617 Northwest Highway, Chicago, IL 60646-6135

(773) 775-8400 • Fax: (773) 775-5968 • Toll Free (888) 372-0465

e-mail: customerservice@enmco.com

ISO 9001:2000 web site: www.enmco.com